

# JGC-065A

## J SERIES AC CROSSFLOW FAN



VOLTAGE	120V~230V
BEARINGS	Ball Bearings
MOTOR	AC Capacitor Type 1ø 4p
IMPELLER	Aluminum Alloy
LENGTH (C)	Min 15.7in (399mm), Max 31.5in (799mm)
AIRFLOW	155~353 CFM (4.4~10.0 m³/min)
OPERATING TEMP	0°C~45°C
OPERATING LIFE	30,000 hours @ 40°C

Model Number	inches (mm)			V	Hz	A	W	RPM	Pressure (P)		Airflow (Q)		dBA	kg
	A	B	C						mmAq	inH <sub>2</sub> O	m³/min	CFM		
JGC-06530A1223-3B	12.6 (320)	13.1 (332)	15.7 (399)	120	60	0.26	27	1650	3.6	0.14	5.2	184	46	1.80
				220	50/60	0.13/0.14	22/25	1400/1600	2.7/3.5	0.11/0.14	4.5/4.9	159/173	42/45	
				230	50	0.14	24	1400	2.7	0.11	4.4	155	42	
JGC-06536A1223-3B	15.0 (380)	15.4 (392)	18.1 (459)	120	60	0.27	29	1600	3.5	0.14	6.3	222	45	1.90
				220	50/60	0.13/0.15	23/27	1350/1500	2.7/3.4	0.11/0.13	5.4/5.9	191/208	44/45	
				230	50	0.14	25	1350	2.7	0.11	5.4	191	44	
JGC-06542A1223-3B	17.3 (440)	17.8 (452)	20.4 (519)	120	60	0.27	30	1550	3.3	0.13	6.8	240	47	2.00
				220	50/60	0.14/0.15	24/27	1350/1500	2.7/3.4	0.11/0.13	5.9/6.3	208/222	43/46	
				230	50	0.14	25	1350	2.7	0.11	5.9	208	43	
JGC-06550A1223-3B	20.4 (520)	20.1 (532)	23.6 (599)	120	60	0.28	30	1500	3.6	0.14	8.2	290	47	2.10
				220	50/60	0.14/0.15	24/28	1300/1400	2.7/3.5	0.11/0.14	6.8/7.1	240/251	43/46	
				230	50	0.14	26	1300	2.7	0.11	6.8	240	43	
JGC-06560A1223-3B	24.4 (620)	24.9 (632)	27.5 (699)	120	60	0.35	38	1500	3.4	0.13	9.2	325	48	2.30
				220	50/60	0.17/0.19	30/35	1300/1350	2.7/3.3	0.11/0.13	8.2/8.6	290/304	44/45	
				230	50	0.18	33	1300	2.7	0.11	8.2	290	44	
JGC-06570A1223-3B	28.3 (720)	28.8 (732)	31.5 (799)	120	60	0.36	38	1450	3.3	0.13	10.0	353	47	2.40
				220	50/60	0.17/0.19	31/35	1250/1300	2.4/3.2	0.09/0.13	9.1/9.3	321/328	43/44	
				230	50	0.18	34	1300	2.5	0.10	9.3	328	43	

