

JL3-030A

J SERIES DC CROSSFLOW FAN



VOLTAGE	12V, 24V
BEARINGS	Ball Bearings
MOTOR	DC Brushless Type 3-phase
IMPELLER	Aluminum Alloy
LENGTH (C)	Min 11.3in (288mm), Max 16.0in (406mm)
AIRFLOW	46~95 CFM (1.3~2.7 m³/min)
OPERATING TEMP	0°C~45°C
OPERATING LIFE	30,000 hours @ 40°C

Model Number		inches (mm)				V	A	RPM	Pressure (P)		Airflow (Q)		dBA	g
		A	B	C	D				mmAq	inH ₂ O	m³/min	CFM		
JL3-03024A12L-3B	①	9.6	10.0	11.3	1.2	12	0.22	2800	1.7	0.07	1.3	46	37	210
JL3-03024A24L-3B	①	(244)	(254)	(288)	(31)	24	0.13							
JL3-03030A12L-3B	②	12.0	12.4	13.7	1.2	12	0.25	2600	1.5	0.06	1.5	53	36	230
JL3-03030A24L-3B	②	(304)	(314)	(348)	(31)	24	0.14							
JL3-03035A12L-3B	③	14.1	14.4	15.8	1.2	12	0.27	2500	1.4	0.05	1.8	64	35	260
JL3-03035A24L-3B	③	(357)	(367)	(401)	(31)	24	0.15							
JL3-03024A12H-3B	④	9.6	10.0	11.5	1.5	12	0.61	4250	4.8	0.19	2.0	71	49	260
JL3-03024A24H-3B	④	(244)	(254)	(293)	(38)	24	0.45							
JL3-03030A12H-3B	⑤	12.0	12.4	13.9	1.5	12	0.67	4100	4.4	0.17	2.4	85	48	290
JL3-03030A24H-3B	⑤	(304)	(314)	(353)	(38)	24	0.45							
JL3-03035A12H-3B	⑥	14.1	14.4	16.0	1.5	12	0.72	3950	3.5	0.14	2.7	95	47	320
JL3-03035A24H-3B	⑥	(357)	(367)	(406)	(38)	24	0.45							

