

JM3-060A

J SERIES DC CROSSFLOW FAN



VOLTAGE	24V
BEARINGS	Ball Bearings
MOTOR	DC Brushless Type 3-phase
IMPELLER	Aluminum Alloy
LENGTH (C)	Min 14.6in (370mm), Max 37.5in (953mm)
AIRFLOW	117~290 CFM (3.3~8.2 m ³ /min)
OPERATING TEMP	0°C~45°C
OPERATING LIFE	30,000 hours @ 40°C

Model Number		inches (mm)			V	A	RPM	Pressure (P)		Airflow (Q)		dBA	kg
		A	B	C				mmAq	inH ₂ O	m ³ /min	CFM		
JM3-06030A24-3B	①	12.2 (310)	12.8 (325)	14.6 (370)	24	0.53	2650	2.5	0.10	3.3	117	45	0.95
JM3-06036A24-3B	②	14.6 (370)	15.2 (385)	16.9 (430)	24	0.58	2600	2.5	0.10	3.9	138	45	1.00
JM3-06042A24-3B	③	16.9 (430)	17.5 (445)	19.3 (490)	24	0.63	2550	2.4	0.09	4.6	162	44	1.10
JM3-06052A24-3B	④	20.9 (530)	21.5 (545)	23.2 (590)	24	0.69	2450	2.3	0.09	5.6	198	43	1.25
JM3-06060A24-3B	⑤	24.0 (610)	24.6 (625)	26.4 (670)	24	0.73	2400	2.3	0.09	6.2	219	43	1.35
JM3-06070A24-3B	⑥	28.0 (710)	28.5 (725)	30.3 (770)	24	0.79	2350	2.2	0.08	6.9	244	42	1.45
JM3-6042X2A24-3B	⑦	34.3 (870)	34.8 (885)	37.5 (953)	24	0.86	2350	2.2	0.08	8.2	290	42	1.90

