

JQ3-065A

J SERIES DC CROSSFLOW FAN



VOLTAGE	24V
BEARINGS	Ball Bearings
MOTOR	DC Brushless Type 3-phase
IMPELLER	Aluminum Alloy
LENGTH (C)	Min 9.8in (250mm), Max 19.3in (490m)
AIRFLOW	78~180 CFM (2.2~5.1 m ³ /min)
OPERATING TEMP	0°C~45°C
OPERATING LIFE	30,000 hours @ 40°C

Model Number		inches (mm)			V	A	RPM	Pressure (P)		Airflow (Q)		dBA	g
		A	B	C				mmAq	inH ₂ O	m ³ /min	CFM		
JQ3-06518A24-3B	①	7.1 (180)	6.7 (172)	9.8 (250)	24	0.20	1400	2.8	0.11	2.2	78	44	740
JQ3-06524A24-3B	②	9.4 (240)	9.1 (232)	12.2 (310)	24	0.23	1300	2.7	0.11	2.9	102	43	810
JQ3-06530A24-3B	③	11.8 (300)	11.5 (292)	14.6 (370)	24	0.27	1250	2.6	0.10	3.8	134	43	930
JQ3-06536A24-3B	④	14.2 (360)	13.9 (352)	16.9 (430)	24	0.29	1200	2.4	0.09	4.4	155	42	1050
JQ3-06542A24-3B	⑤	16.5 (420)	16.2 (412)	19.3 (490)	24	0.32	1150	2.3	0.09	5.1	180	41	1110

