

# JAC-110

## J SERIES AC AIR CURTAIN



VOLTAGE	110V~230V
BEARINGS	Ball Bearings
MOTOR	AC
IMPELLER	Aluminum Alloy
LENGTH (C)	Min 35.4in (900mm), Max 59.1in (1500m)
AIRFLOW	989~1942 CFM (28~55 m³/min)
OPERATING TEMP	0°C~45°C
OPERATING LIFE	30,000 hours @ 40°C

Model Number	inches (mm)	Speed	V	Hz	A	W	RPM	Distance (m)	Airflow (Q)		dBA	kg
	A								m³/min	CFM		
JAC-1103-11	35.4 (900)	Hi/Low	110	60	1.18/0.92	128/102	11.5/9.5	3.5/3.0	33/28	1165/989	57/53	8.50
JAC-1103-22	35.4 (900)	Hi/Low	220	60	0.60/0.47	131/101	11.5/9.5	3.5/3.0	33/28	1165/989	57/53	8.50
JAC-1103-23	35.4 (900)	Hi/Low	230	50	0.54/0.40	120/92	11.5/9.5	3.5/3.0	33/28	1165/989	57/53	8.50
JAC-1104-11	47.2 (1200)	Hi/Low	110	60	1.72/1.34	190/150	11.5/9.5	3.5/3.0	44/37	1554/1307	59/55	10.50
JAC-1104-22	47.2 (1200)	Hi/Low	220	60	0.85/0.67	191/148	11.5/9.5	3.5/3.0	44/37	1554/1307	59/55	10.50
JAC-1104-23	47.2 (1200)	Hi/Low	230	50	0.74/0.61	170/140	11.5/9.5	3.5/3.0	44/37	1554/1307	59/55	10.50
JAC-1105-11	59.1 (1500)	Hi/Low	110	60	2.24/1.62	242/180	11.5/9.5	3.5/3.0	55/46	1942/1624	60/56	12.50
JAC-1105-22	59.1 (1500)	Hi/Low	220	60	1.16/0.87	257/195	11.5/9.5	3.5/3.0	55/46	1942/1624	60/56	12.50
JAC-1105-23	59.1 (1500)	Hi/Low	230	50	0.91/0.73	215/175	11.5/9.5	3.5/3.0	55/46	1942/1624	60/56	12.50

