



RA24BL001-B40

BRUSHLESS DC CENTRIFUGAL BLOWER SERIES

DUAL WHEEL DESIGN

12V, 24V

571~630 CFM (970~1070 m³/h)

Dual Ball Bearings

Housing: PA66 + 30% GF, UL94-V0

Impeller: PA66 + 30% GF, UL94-V0

Operating Temperature: -40°C ~ +70°C

Operating Life: 25,000 hours

Locked Rotor/Short-Circuit/Over-Voltage Protection

IP68 Dust & Moisture Protection

RoHS

Model Number	Voltage (V)	Part Number	Current (A)	No. Speeds	Airflow (Q) (CFM)	Airflow (Q) (m ³ /h)
RA12BL001-B40-3SP-02	12	02.12.01	15.0	3	571	970
RA12BL001-B40-VSP-02	12	02.12.02	15.0	Variable	571	970
RA24BL001-B40-3SP-02	24	02.24.01	9.5	3	630	1070
RA24BL001-B40-VSP-02	24	02.24.02	10.0	Variable	630	1070
RA24BL001-B40-VSP-02E	24	02.24.02.9	10.0	Variable	630	1070
RA24BL001-B40-3SP-02-F	24	02.24.31	9.5	3	630	1070

